



Quality

**CITY**

**CITY-C00**

<b>Date</b> 17/09/2013	
<b>Backing</b> 70% Polyester / 30% Cotton <b>Coating</b> 100% Polyurethane	
<b>Composition Coating</b> 280 g/m <sup>2</sup> <b>Backing</b> 180 g/m <sup>2</sup>	
<b>Total</b>	460 g/m <sup>2</sup> ± 20 g/m <sup>2</sup>
<b>Thickness</b>	0,85 ± 0.1 mm
<b>Tensile strength</b> ISO 1421 1998 length >50 daN/ 5 cm width >35 daN/ 5 cm	
<b>Tear strength</b> ISO 4674-01 2003 length >3 daN width >3 daN	
<b>Seam resistance</b> ISO 13934-01 1999 length >32 daN width >38 daN	
<b>% Elongation under 30N/5cm</b> length >1,8 % width >6,5 %	
<b>Coating to fabric adhesion</b> ISO 2411 2000 >3 daN/5cm	
<b>Flex resistance</b> ISO 5402 1:2003 no quality loss after 50000	
<b>Combined shear flexing and rubbing</b> ISO 5981: 2008 no quality loss after 30000	
<b>Abrasion resistance (Martindale)</b> EN ISO 5470-2 2003 >100000	
<b>Hydrolysis</b> Jungle test no loss of quality after 3 weeks	
<b>Colour fastness to light</b> EN ISO 105 B02 1994 min. 5-6	
<b>Flame retardancy</b> BS 5852 2006 Crib 5 Centexbel 13.03163.02 (12/07/2013) <b>NF P 92-503 : 1995</b> M3 Centexbel 13.03163.03 (12/07/2013)	
<b>EN 1021-1 : 2006</b> Engaged in testing	
<b>EN 1021-2 : 2006</b> Engaged in testing	
<b>Cleaning</b> We recommend to clean this article with water and soap only. Cleaning products containing alcohol, solvent, bleach or abrasive products can damage this product.	
<b>Other</b> <b>DMF-content</b> < 0,1% Centexbel 13.03502.01 (02/08/2013)	

**Remarks**

All the specifications given in this document have been tested in accredited laboratories or in our own laboratory using officially calibrated measuring equipment.

This datasheet is valid for five years after the date of publication. However, we guarantee that the item has been produced with the same ingredients and ISO-9000 procedures were strictly complied with. In the event that any modifications may have been applied during this period, all the properties were retested.

The items delivered comply with the specifications stated in this datasheet. In principle, we do not guarantee properties or characteristics that are not included in it.

Slight colour variations between deliveries are possible. We recommend that you always process items from different deliveries separately. This item complies with the most recent REACH specifications.



APPROVAL : CEO